



LU4000 ST-2110 RECEIVER

Building a native LRT™
IP-to-IP broadcasting
powerhouse




A single 4K or quad HD video decoder for
combining LRT™ into your SMPTE ST-2110
broadcasting facility through a single device


SCALABILITY.

REDUNDANCY.

SLOTS IN PERFECTLY.



A native LRT™ IP-to-IP streaming method



Key Features


- ST-2022-7 redundancy
- NMOS support (IS 04/IS 05)
- 4K single feed
- Four full HD feeds

The confidence you need to receive your ST-2110 feeds



Slots into your environment

- Suitable for various network architectures
- Integrated hardware PTP (Precision Time Protocol) for ST 2059-2
- Built-in management system support



Unlimited scalability

- Contributing to greater workflow efficiency
- Enabling full interoperability



Future-ready

- Advanced product architecture
- Supports ST-2110 workflow simplifications as they roll out
- Integral element of LiveU EcoSystem


Technical Specifications

FORM FACTOR	1U rackmount server
SOFTWARE	Pre-installed with LiveU LRT™ decoder software
VIDEO DECODER	H.265/HEVC, H.264
ST-2110 MEDIA INTERFACES	2x SFP ports, 25 GB (Transceivers not included)
MEDIA OUTPUT PROTOCOLS	ST 2110, RTMP for streaming to CDNs or social media, MPEG-TS, SRT, LiveU Matrix and NDI
SUPPORTED RESOLUTIONS	2160p60/50/30/25/24, 1080p60/50/30/25/24, 1080i60/50, 720p60/50, PAL, NTSC
NETWORK INTERFACES	2 X 25 Gigabit ethernet
POWER SOURCES	110-240V 50/60HZ
CONTROL	Full control using both NMOS system (IS 04 /IS 05) and cloud management via LiveU Central
PREVIEW	Transcodes and outputs preview via LiveU Central
DIMENSIONS	1.7" (43mm) Height, 17.2" (437mm) Width, 19.8" (503mm) Depth
WEIGHT	21 lbs / 9.5 Kg






Live and **Unlimited**



www.liveu.tv | www.facebook.com/liveu.fans | www.twitter.com/liveu

LiveU Inc. | 2 University Plaza, Suite 505, Hackensack, New Jersey 07601, USA | Tel: 1-(201)-742-5229 | www.liveu.tv/contact-us